

FICHA TÉCNICA

**Bombas sumergibles hidráulicas
D & D PUMPS**

Bombas sumergibles hidráulicas



Unidad motriz hidráulica 800D para bomba 12 "



| | Bomba 4" | Bomba 6" | Bomba 8" | Bomba 12" |
|---------------------|--------------------------------|--------------------------------|---------------------------------|---------------------------------|
| Peso | 62 kg | 68 kg | 115 kg | 340 kg |
| Potencia hidráulica | 30 bhp@1800 rpm | 61 bhp@1800 rpm | 61 bhp 1800 rpm | 192 bhp 1800 rpm |
| Máximo de sólidos | 3" | 3" | 4" | 4" |
| Capacidad a 5 mt | 50 lt/s | 144 lt/s | 180 lt/s | 490 lt/s |
| Capacidad a 10 mt | 42 lt/s | 120 lt/s | 165 lt/s | 470 lt/s |
| Capacidad a 15 mt | 30 lt/s | 76 lt/s | 140 lt/s | 395 lt/s |
| Capacidad a 20 mt | 15 lt/s | 10 lt/s | 196 lt/s | 270 lt/s |
| Unidad Motriz | Mac Hydraulics 250 | Hydra Tech HT60DCV | Pioneer 8" | D&D 800D |
| Motor | Kubota V1505 | Deutz D914L04 | John Deere 4045TF150 4.5L | John Deere 6081TP2-200 |
| Potencia | 30 hp@ 2300 RPM | 70 hp@ 2300 RPM | 100hp@1.800rpm | 192 BHP @ 1800 RPM |
| Consumo | 0.17lt/hp- hr@1.800rpm 5 lt/hr | 0.17lt/hp- hr@1.800rpm 8 lt/hr | 0.17lt/hp- hr@1.800rpm 17 lt/hr | 0.17lt/hp- hr@1.800rpm 32 lt/hr |